

Flowmeter

Silbermann flowmeter is a back-pressure compensated for all type of inhalation therapy

The flowmeter is unbreakable, with top cover and measuring tube made of clear transparent polycarbonate.



Features & Benefits

- Standard model flow rate: 0-15 LPM
- Low flow model flow rate: 0-7 LPM
- Both types with Oxygen DISS male outlet
- Non-linear scale enabling a clearer & accurate operation in the working range
- Different probes available
- Reliable, accurate and easy to use
- Non erasable laser engraved product info
- Rail mounted flowmeter includes:
1 meter plastic medical tubing, universal clamp and probe.



Technical Data

- Main Materials:
 - Body: Anodized Aluminum*
 - Cover: Transparent non-breakable polycarbonate.
 - Measuring tube: Transparent non-breakable polycarbonate

* Brass available on special request

Silbermann's Quality Management System:

- EN ISO 13485-2016
- ISO 9001-2015
- CE marked





Catalogue Numbers - Flowmeter with probe

Type of Male Adapter	0-15 LPM		0-7 LPM
	Oxygen Cat. No.	Air Cat. No.	Oxygen Cat. No.
Silbermann- Ohio	4110000	4148000	4107000
ENV 737-6	4110100	4148110	4107100
DIN 13260-2	4261000	4264000	4265000
Puritan Bennett type	4145000	4150000	4109000
BS5682	4110105	TBD	TBD
DISS	4112000	4147000	4134500
Without probe (1/8 NPT female thread)	4501100	4502100	4107010



Catalogue Numbers - Rail Mounted Flowmeter with probe

Type of Inlet\ Male Adapter	0-15 LPM		0-7 LPM
	Oxygen Cat. No.	Air Cat. No.	Oxygen Cat. No.
Silbermann- Ohio	4120001	4235000	4119001
ENV 737-6	4120101	4235005	4120110
DIN 13260-2	4233100	4235005	4225100
Puritan Bennett type	4233000	4237000	4225000
BS5682	TBD	TBD	TBD
DISS	4231000	4511000	TBD
Without probe (1/8 NPT female thread)	4120100	TBD	TBD

* Available on customer request



Related Products



Humidifier*
P.N - 4101100



Complete DISS
metal nut assembly
for Oxygen
P.N - 2229000



Oxygen DISS,
plastic nut & gland,
for one patient use
P.N - 2261000

* Silbermann's reusable Humidifiers are made of polycarbonate tops, polysulfone jars and are autoclavable at 270°F (132°C).
Jars capacity - 500cc.
Includes safety valve 2 PSI
Inlet - DISS nut assembly.
Includes two flow outlets: 3 - 6mm bushed nipple & 22mm corrugated tube.
ISO color available on request



Assembly - Oxygen Unit



Rail Mounted Oxygen Unit



Oxygen Unit

Distributed By:

SILBERMANN Technologies Ltd.

Address: #5 Harakevet st. POB 4605, Petah-Tikva, 4900715, ISRAEL

Tel: +972-3-9309186 | Fax: +972-3-9315721

E-Mail: info@silbermnn.com, www.silbermnn.com