

Humidifier

Silbermann Humidifier is used to moisturize the Oxygen delivered to the patient. Our re-usable humidifier is made of polycarbonate top autoclavable at 250°F (121°C), polysulfone jar autoclavable at 270°F (132°C) and is environmentally friendly.

Designed to alleviate the patient breathing and provide the patient with continuous and reliable inhalation therapy.



Features & Benefits

- Reusable & Ecofriendly
- Durable - Robust design for long lasting usage
- Easy to clean
- Two different flow outlets for various treatments
- Pressure safety valve (Optional)

Silbermann's Quality Management System:

- EN ISO 13485-2016
- ISO 9001-2015
- CE marked



Technical Data

- Main Materials:
 - Top Cover: Polycarbonate
 - Jar: Transparent polysulfon
- Jar Capacity: 500cc.
- Inlet: DISS Oxygen nut assembly
- With/Without safety valve - 2 PSI
- Flow Outlets: 3- 6mm bushed nipple & 22mm corrugated tube
- Top autoclavable at 250°F (121°C)
- Jar autoclavable at 270°F (132°C)



Assembly - Oxygen Unit (Humidifier+ Flowmeter+ probe)



Rail Mounted Oxygen Unit



Oxygen Unit



Catalog No.

Description	Part No.
Humidifier with safety valve	4101200
Humidifier without safety valve	4101100

Distributed By:

SILBERMANN Technologies Ltd.

Address: #5 Harakevet st. POB 4605, Petah-Tikva, 4900715, ISRAEL
 Tel: +972-3-9309186 | Fax: +972-3-9315721
 E-Mail: info@silbermann.com, www.silbermann.com